

Tranax 4000T



Through The Wall Solution

The all new **Tranax 4000T** ATM provides an economical, high performance through-the-wall solution. Designed and built with compact **modular** components and engineered for **easy installation**.

The 4000T offers a host of high-end features including a **10.4" High-Bright Color LCD** supporting custom screen advertisements and communication via **56K Modem** or integrated **Ethernet (SSL)**.

The Tranax 4000T is **TDES** and **ADA** compliant out of the box, including a **PCI/VISA/Interac certified encrypting PIN pad (EPP)**, a voice guidance system, and lighted action indicators.

TRANAX

Discover the Tranax Difference

Tranax 4000T

TRANAX
www.tranax.com

INTEGRATED ILLUMINATED TOPPER

Integrated illuminated topper
for creating high visibility
and attracting customers

HIGH-BRIGHT MONITOR

7 inch diagonal 32-bit color, backlit
TFT LCD panel
800 x 600 SVGA resolution

ADA

Accessible keypad layout
Voice guidance
Lighted action indicators

TRANAX

PRINTER

3 1/8" Thermal receipt printer.
Can print custom graphic

CARD READER

Manual insert (dip) magnetic card reader
EMV (optional)

KEYPAD

16-key alphanumeric keypad
VISA/Interac PCI certified
Triple DES (TDES) compliant
Encrypting PIN pad (EPP)

CPU

Intel XScale® 32-bit CPU
Windows® CE operating system

REAR SERVICE PANEL

Perform Operator Tasks and Diagnostics

COMMUNICATION

56K dial-up modem or Ethernet (TCP/IP)
On-board SSL Encryption

CASH DISPENSER

Sliding cash dispensing unit for easy service
▪ 1,000 note removable cassette

SECURITY

UL 291 Business Hour listed
Electronic lock
Cencon Lock (optional)

SPECIFICATIONS

Dimensions

33" H 24" W 17" D

Weight: 250 lbs

*optional dispensers will increase overall weight

Operating Environment:

Temperature range: 40°F-95°F

Relative humidity: Non-condensing - 15%-85%

Options and Upgrades:

High-bright topper

INSTALLATION

The Tranax 4000T comes with a steel pedestal which can be adjusted from 25" to 35". The pedestal carries the entire weight of the machine so you can install the 4000T in thin walls or facades.